Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Sources | | | | | | | |
|--|----------------|-------------------------|--|--------------|--|--|--|
| Supplier's name or trade mark: ULTRALUX | | | | | | | |
| Supplier's address: - | | | | | | | |
| Model identifier: NGW283560W | | | | | | | |
| Type of light source: | | | | | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS | | | |
| Light source cap-type | | - | | | | | |
| (or other electri | c interface) | | | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | No | | | |
| Colour-tuneable light source: | | No | Envelope: | - | | | |
| High luminance light source: | | No | | | | | |
| Anti-glare shield | d: | No | Dimmable: | Yes | | | |
| Product parameters | | | | | | | |
| Parameter | | Value | Parameter | Value | | | |
| General product parameters: | | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 5 | Energy efficiency class | F | | | |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 540 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 | | | |
| On-mode power (P _{on}), expressed in W | | 4,8 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | | |
| Outer dimen- | Height | - | Spectral power dis- | See image | | | |
| sions without separate con- trol gear, light- ing control | Width Depth | - | tribution in the range 250 nm to 800 nm, at full-load | in last page | | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,313 | | | |
| | | nates (x and y) | 0,337 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 5 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,93 | | | | | |

(a)'-': not applicable; (b)'-': not applicable;