

## DATA SHEET

LED SLIM FLOODLIGHT 10W, 4200K, 220V, IP65, NEUTRAL LIGHT, SMD2835

SPD1042



## DESCRIPTION

The SPD floodlights are a line for general purpose lighting, replacing the traditional halogen floodlights. The LED technology ensures substantial energy savings and less maintenance costs. The floodlight's bracket allows it to be mounted under a given angle, on a wall or other surface.

## APPLICATION

Lighting for industrial and commercial premises  
Working areas  
Sport's facilities  
Facades

## DATA SHEET

### Light technical information

---

- Efficiency: 80 lm/W
- Rated luminous flux: 800 lm
- Beam angle: 120 °
- Color Rendering Index (CRI): >80
- Correlated Color Temperature (CCT): 4200 K
- Photometric file (.LDT): ldt. file is available

### Electrotechnical information

---

- Voltage: 220-240 V AC
- Frequency: 50-60 Hz
- Power factor: PF > 0.9
- Power: 10 W
- Class: I
- Driver: Built-in, non-dimmable

### Basic information

---

- Type of protection: IP65
- Working temperature: -20 °C ÷ +40 °C
- On/Off Cycles: >15 000
- Lumen Maintenance L80B50: >25 000 h
- Dimensions: 110/78/35 mm
- Warranty: 2 years